







Assortment

	Order no.	Product	Material class 2*			Material class 4*			Material class 5*		
			EUR excl. VAT	EUR excl. VAT	EUR excl. VAT	EUR excl. VAT	EUR excl. VAT	EUR excl. VAT	EUR excl. VAT	EUR excl. VAT	EUR excl. VAT
	206 00 200 171	ALU-SMART ∅ 200 without flounce	—	209.—	329.—	—	209.—	329.—	—	209.—	329.—
	206 00 220 171	ALU-SMART ∅ 220 without flounce	—	234.—	371.—	—	234.—	371.—	—	234.—	371.—
	206 00 250 171	ALU-SMART ∅ 250 without flounce	—	251.—	388.—	—	251.—	388.—	—	251.—	388.—
	206 00 300 171	ALU-SMART ∅ 300 without flounce	—	335.—	496.—	—	335.—	496.—	—	335.—	496.—
	206 00 212 171	ALU-SMART 210 × 150 without flounce	—	251.—	379.—	—	251.—	379.—	—	251.—	379.—
	206 00 252 171	ALU-SMART 250 × 200 without flounce	—	318.—	479.—	—	318.—	479.—	—	318.—	479.—
	206 00 201 171	ALU-SMART 200 × 200 without flounce	—	318.—	471.—	—	318.—	471.—	—	318.—	471.—
	206 00 241 171	ALU-SMART 240 × 240 without flounce	—	335.—	496.—	—	335.—	496.—	—	335.—	496.—
	206 00 200 171	ALU-SMART <i>easy</i> ∅ 200 without flounce	125.—	—	—	—	—	—	—	—	—
	206 00 220 171	ALU-SMART <i>easy</i> ∅ 220 without flounce	142.—	—	—	—	—	—	—	—	—
	206 00 250 171	ALU-SMART <i>easy</i> ∅ 250 without flounce	150.—	—	—	—	—	—	—	—	—
	206 00 300 171	ALU-SMART <i>easy</i> ∅ 300 without flounce	192.—	—	—	—	—	—	—	—	—
	206 00 212 171	ALU-SMART <i>easy</i> 210 × 150 without flounce	142.—	—	—	—	—	—	—	—	—
	206 00 252 171	ALU-SMART <i>easy</i> 250 × 200 without flounce	167.—	—	—	—	—	—	—	—	—
	206 00 201 171	ALU-SMART <i>easy</i> 200 × 200 without flounce	167.—	—	—	—	—	—	—	—	—
	206 00 241 171	ALU-SMART <i>easy</i> 240 × 240 without flounce	192.—	—	—	—	—	—	—	—	—

*Different colours area available in each material class. The higher the material class the more robust and durable the material is.
Please ask your distribution partner about the GLATZ material collection.

Accessories

Order no.	Product	EUR excl. VAT
Fixing option Z (support tube Z absolutely necessary)		
350 01 109 532	Concrete base Z, 30 kg, Ø 47 × 8.5 cm	50.–
350 01 109 529	Concrete base Z, 40 kg, Ø 60 × 8.5 cm	66.–
350 01 109 460	Granite base Z, 40 kg, Ø 53 × 7 cm, natural stone	100.–
350 01 109 440	³ Granite base Z, 55 kg, 55 × 55 × 9 cm, natural stone, with castors and retractable handle	139.–
350 01 100 210	Steel base Z, 40 kg, 58.5 × 58.5 × 2 cm, galvanised steel	374.–
350 01 205 000	Wall bracket Z, 180 mm, galvanised steel	100.–
350 01 205 400	Lawn spike Z, 85 × 150 × 350, galvanised steel	41.–
350 01 201 010	Support tube Z, Ø 35/38 – 39 mm, galvanised steel	55.–
350 01 201 100	Support tube Z, Ø 35/38 – 39 mm, high-grade steel 1.4301/304	100.–
³Base with castors Z (support tube Z absolutely necessary)		
350 01 102 900	Base with castors Z, 55 kg, 65 × 65 × 11 cm, cast concrete decor	374.–
³Base with castors (Weight set absolutely necessary)		
350 01 102 300	Base frame with castors 45 kg, 50 × 50 × 12 cm, anthracite, with support tube Ø 35/38 – 39 mm, polished aluminium (Base frame ca. 13 kg)	248.–
350 01 103 300	Weight Set, 4 pieces 35001105300, concrete, for base with castors 45 kg (Weight Set ca. 32 kg)	80.–
350 01 602 300	Protective cover for base with castors 45 kg	58.–
350 01 102 400	Base frame with castors 60 kg, Ø 61 × 12 cm, anthracite, with support tube Ø 35/38 – 39 mm, polished aluminium (Base frame ca. 17 kg)	290.–
350 01 103 400	Weight Set, 4 pieces 35001105400, concrete, for base with castors 60 kg (Weight Set ca. 43 kg)	97.–
350 01 602 400	Protective cover for base with castors 60 kg	66.–
Fixing option BT (Connection tube BT absolutely necessary)		
350 01 206 100	Ground socket BT, galvanised steel	79.–
350 01 206 210	Connection tube BT Ø 35/38 – 39 mm, galvanised steel	66.–
Different fixing options		
350 01 252 005	Wall consoles U for the table top, Ø 31 – 40 mm, high-grade steel 1.4301/304, for horizontal flat railing, square profile up to 120 mm	134.–
Protective cover, coated polyester fabric		
350 01 609 971	Protective cover with zip and rod	41.–
350 01 609 973	10 pieces, protective cover with zip and rod	388.–
Miscellaneous items		
350 01 557 950	Rechargeable battery light Osyrion 6 for pole Ø 30 – 50 mm, battery charger with european plug (type C) included 1 accumulator included	124.–
350 01 557 910	Rechargeable battery light Osyrion 4 for pole Ø 30 – 50 mm, battery charger with european plug (type C) included 1 accumulator included	83.–
350 01 557 920	Spare accu, 3.6 V, 2500 mAh (for Osyrion 4 & 6)	38.–

³ only suitable for smooth, joint free surface coverings