

## Assortment

	Order no.	Product	Material class 2*			Material class 4*			Material class 5*		
						USD excl. VAT	USD excl. VAT	USD excl. VAT	USD excl. VAT	USD excl. VAT	USD excl. VAT
○	204 00 270 171	ALU-TWIST Ø 270 without flounce				—	457.–	619.–			
	204 00 300 171	ALU-TWIST Ø 300 without flounce				—	486.–	717.–			
	204 00 330 171	ALU-TWIST Ø 330 without flounce				—	525.–	775.–			
□	204 00 213 171	ALU-TWIST 210 × 150 without flounce				—	418.–	580.–			
	204 00 253 171	ALU-TWIST 250 × 200 without flounce				—	486.–	678.–			
□	204 00 241 171	ALU-TWIST 240 × 240 without flounce				—	525.–	726.–			
○	204 00 270 171	ALU-TWIST <i>easy</i> Ø 270 without flounce				253.–	—	—			
	204 00 300 171	ALU-TWIST <i>easy</i> Ø 300 without flounce				282.–	—	—			
	204 00 330 171	ALU-TWIST <i>easy</i> Ø 330 without flounce				311.–	—	—			
□	204 00 213 171	ALU-TWIST <i>easy</i> 210 × 150 without flounce				253.–	—	—			
	204 00 253 171	ALU-TWIST <i>easy</i> 250 × 200 without flounce				292.–	—	—			
□	204 00 241 171	ALU-TWIST <i>easy</i> 240 × 240 without flounce				311.–	—	—			

\*Different colours are available in each material class. The higher the material class the more robust and durable the material is.  
Please ask your distribution partner about the GLATZ material collection.

## Accessories

Order no.	Product	USD excl. VAT
<b>Fixing option Z (support tube Z absolutely necessary)</b>		
350 01 109 529	Concrete base Z, 40 kg, Ø 60 × 8.5 cm	77.–
350 01 109 528	Concrete base Z, 55 kg, Ø 60 × 11 cm	87.–
350 01 109 460	Granite base Z 40 kg, Ø 53 × 7 cm, natural stone	122.–
350 01 109 440	<sup>3</sup> Granite base Z 55 kg, 55 × 55 × 9 cm, natural stone, with castors and retractable handle	165.–
350 01 100 210	Steel base Z 40 kg, 58.5 × 58.5 × 2 cm, galvanised steel	447.–
350 01 100 310	Add-on weight 30 kg, 57.5 × 57.5 × 1.7 cm, galvanised steel	292.–
350 01 205 000	Wall bracket Z, 180 mm, galvanised steel	122.–
350 01 205 400	Lawn spike Z, 85 × 150 × 350, galvanised steel	48.–
350 01 201 010	Support tube Z, Ø 35/38 – 39 mm, galvanised steel	67.–
350 01 201 100	Support tube Z, Ø 35/38 – 39 mm, high-grade steel 1.4301/304	122.–
<b><sup>3</sup>Base with castors Z (support tube Z absolutely necessary)</b>		
350 01 102 900	Base with castors Z, 55 kg, 65 × 65 × 11 cm, cast concrete decor	483.–
<b><sup>3</sup>Base with castors (Weight set absolutely necessary)</b>		
350 01 102 300	Base frame with castors 45 kg, 50 × 50 × 12 cm, anthracite, with support tube Ø 35/38 – 39 mm, polished aluminium (Base frame ca. 13 kg)	307.–
350 01 103 300	Weight Set, 4 pieces 35001105300, concrete, for base with castors 45 kg (Weight Set ca. 32 kg)	97.–
350 01 602 300	Protective cover for base with castors 45 kg	67.–
350 01 102 400	Base frame with castors 60 kg, Ø 61 × 12 cm, anthracite, with support tube Ø 35/38 – 39 mm, polished aluminium (Base frame ca. 17 kg)	346.–
350 01 103 400	Weight Set, 4 pieces 35001105400, concrete, for base with castors 60 kg (Weight Set ca. 43 kg)	116.–
350 01 602 400	Protective cover for base with castors 60 kg	77.–
<b>Fixing option BT (Connection tube BT absolutely necessary)</b>		
350 01 206 100	Ground socket BT, galvanised steel	97.–
350 01 206 210	Connection tube BT, Ø 35/38 – 39 mm, galvanised steel	77.–
<b>Different fixing options</b>		
350 01 252 005	Wall consoles U for the table top, Ø 31 – 40 mm, high-grade steel 1.4301/304, for horizontal flat railing, square profile up to 120 mm	161.–
<b>Protective cover, coated polyester fabric</b>		
350 01 609 971	Protective cover with zip and rod	48.–
350 01 609 973	10 pieces, protective cover with zip and rod	453.–
<b>Miscellaneous items</b>		
350 01 557 950	Rechargeable battery light Osyrion 6 for pole Ø 30 – 50 mm, battery charger with european plug (type C) included 1 accumulator included	145.–
350 01 557 910	Rechargeable battery light Osyrion 4 for pole Ø 30 – 50 mm, battery charger with european plug (type C) included 1 accumulator included	97.–
350 01 557 920	Spare accu, 3.6 V, 2500 mAh (for Osyrion 4 & 6)	48.–

<sup>3</sup> only suitable for smooth, joint free surface coverings