

Assortment

	Order no. Frame sycamore	Order no. Frame hardwood	Product	Material class 2*	Material class 4*	Material class 5*
				EUR excl. VAT	EUR excl. VAT	EUR excl. VAT
○	173 00 300 751		PIAZZINO Ø 300 without flounce	—	651.—	829.—
	173 00 350 751		PIAZZINO Ø 350 without flounce	—	710.—	896.—
□	173 00 301 751		PIAZZINO 300 × 300 without flounce	—	752.—	979.—
○		172 00 300 751	PIAZZINO <i>easy</i> Ø 300 without flounce	251.—	—	—
		172 00 350 751	PIAZZINO <i>easy</i> Ø 350 without flounce	335.—	—	—
□		172 00 301 751	PIAZZINO <i>easy</i> 300 × 300 without flounce	335.—	—	—

Accessories

Order no.	Product	EUR excl. VAT
	Fixing option Z (support tube Z absolutely necessary)	
350 01 109 529	Concrete base Z, 40 kg, Ø 60 × 8.5 cm	66.—
350 01 109 528	Concrete base Z, 55 kg, Ø 60 × 11 cm	75.—
350 01 109 460	Granite base Z 40 kg, Ø 53 × 7 cm, natural stone	100.—
350 01 109 440	³ Granite base Z 55 kg, 55 × 55 × 9 cm, natural stone, with castors and retractable handle	139.—
350 01 100 210	Steel base Z 40 kg, 58.5 × 58.5 × 2 cm, galvanised steel	374.—
350 01 100 310	Add-on weight 30 kg, 57.5 × 57.5 × 1.7 cm, galvanised steel	248.—
350 01 205 000	Wall bracket Z, 180 mm, galvanised steel	100.—
350 01 201 210	Support tube Z, Ø 48/55 mm, galvanised steel	66.—
350 01 201 300	Support tube Z, Ø 48/55 mm, high-grade steel 1.4301/304	117.—
	³Base with castors Z (support tube Z absolutely necessary)	
350 01 102 900	Base with castors Z, 55 kg, 65 × 65 × 11 cm, cast concrete decor	374.—
	Fixing option PX (Connection tube PX absolutely necessary)	
350 01 207 001	Ground socket PX, galvanised steel	80.—
350 01 207 011	Ground socket PX, high-grade steel 1.4301/304	164.—
350 01 206 001	Connection tube PX, Ø 48/55 mm, galvanised steel	75.—
350 01 206 011	Connection tube PX, Ø 48/55 mm, high-grade steel 1.4301/304	125.—
	Protective cover, coated polyester fabric	
350 01 609 968	Protective cover with zip and rod	66.—
	Miscellaneous items	
350 01 557 960	Rechargeable battery light Osyrion 8 for pole Ø 48–68 mm, battery charger with european plug (type C) included, 1 accumulator included	166.—
350 01 557 950	Rechargeable battery light Osyrion 6 for pole Ø 30–50 mm, battery charger with european plug (type C) included, 1 accumulator included	124.—
350 01 557 910	Rechargeable battery light Osyrion 4 for pole Ø 30–50 mm, battery charger with european plug (type C) included, 1 accumulator included	83.—
350 01 557 970	Spare accu, 3.7 V, 4800 mAh (for Osyrion 8)	38.—

³ only suitable for smooth, joint free surface coverings

*Different colours area available in each material class. The higher the material class the more robust and durable the material is.
Please ask your distribution partner about the GLATZ material collection.